

## MULTI FUNCTION DOUBLE BEAM ELECTRONIC DIGITAL HEIGHT GAGE

ISO9001

**Features:**

- Language selection English/Chinese
- Data holding
- Absolute /Relative measurement(ABS)
- In/mm conversion
- OLED screen
- Bluetooth data output
- Auto power off
- Preset function for entering a known value or initial value
- Absolute origin correction
- Zero-setting of display
- Set and determine tolerance
- Batter: 3.7V rechargeable lithium battery (Normal use more than 12 hours on one charge)
- Operating temp.: 0° - 40°
- Relative humidity: ≤80%

Item	Range	Resolution	Accuracy	Price
8528-0012	0-12"/0-300mm	0.0005"/0.01mm	±0.015mm	\$578.00/PC
8528-0024	0-24"/0-600mm	0.0005"/0.01mm	±0.025mm	\$886.00/PC



## ELECTRONIC DIGITAL UNIVERSAL BEVEL PROTRACTOR

ISO9001

**Features:**

- Digital protractor which displays degrees, minutes, seconds and decimal degrees at the same time.
- Measuring range: 0-360°
- Resolution: ±5" or ±0.08°
- LCD display.
- Range selection: 1x360°, 2x180°, 4x90°.
- On/off switch.
- Reset/preset.
- Reversible measurement direction.
- Fine adjustment.
- Power supply: 1 battery (CR2032).



Item # S907-C885  
\$399.00/SET

## THREE -POINT INTERNAL MICROMETER, RATCHET STOP

Range: 0.275 - 0.400"

**Features:**

- Measurement can be taken closer to the bottom of the blind bore, and can be taken into a deep hole with an extension rod.
- Highly durable because of carbide-tipped contact points.
- Ratchet stop.
- Within 4": provided with setting ring.
- Over 0.5": Titanium-plated anvil optional.
- Resolution:  
Within 0.5": 0.0001"  
Over 0.5": 0.0002"




Item	Range	Accuracy	Setting ring	L1	A	Extension rod	Price
3150-1111	0.275-0.350"	±0.00016"	0.275"	2.18"	0.06"	4"	\$315.00/PC
3150-2111	0.350-0.425"	±0.00016"	0.350"	2.18"	0.06"	4"	\$315.00/PC
3150-3111	0.425-0.500"	±0.00016"	0.500"	2.18"	0.06"	4"	\$315.00/PC
3150-4071	0.500-0.650"	±0.00016"	0.650"	3.2"	0.02"	6"	\$258.00/PC
3150-5071	0.650-0.800"	±0.00016"	0.650"	3.2"	0.02"	6"	\$258.00/PC
3150-6071	0.800-1.000"	±0.00016"	1.000"	3.6"	0.02"	6"	\$330.00/PC
3150-7071	1.000-1.200"	±0.00016"	1.000"	3.6"	0.02"	6"	\$330.00/PC
3150-8071	1.200-1.600"	±0.00016"	1.600"	3.88"	0.02"	6"	\$386.00/PC
3150-9071	1.600-2.000"	±0.00020"	1.600"	3.88"	0.02"	6"	\$445.00/PC
3151-0071	2.000-2.500"	±0.00020"	2.500"	4.56"	0.02"	6"	\$469.00/PC
3151-1071	2.500-3.000"	±0.00020"	2.500"	4.56"	0.02"	6"	\$508.00/PC
3151-2071	3.000-3.500"	±0.00020"	3.500"	4.56"	0.02"	6"	\$523.00/PC
3151-3071	3.500-4.000"	±0.00020"	3.500"	4.56"	0.02"	6"	\$558.00/PC

## MICROMETER STAND

**Features:**

- Folding design for portable use
- Clamp can be adjusted and locked in any position

Item #S907-C153  
\$34.00/PC



- 0-1" ultra-precision M-type outside micrometer, with micrometer stand
- EG00-0001 as Page 9



Item #C153-EG01  
\$61.00/SET

- Electronic digital outside micrometer 0-1"/0-25mm, with micrometer Stand
- MD71-0001 as Page 8



Item #C153-MD01  
\$103.00/SET

## ELECTRONIC EDGE FINDER WITH SOUND ALERT 3/4" x 7-1/2" T.I.R WITHIN 0.0002"

**Features:**

- One piece construction for strength and repeat-ability T.I.R within 0.005 mm/0.0002"
- Precision ground on all surfaces
- Quickly locates work edges
- Save time positioning
- Tool steel hardened to HRc 60
- High sensitivity probe for accurate positioning
- Four highly visible lights
- Both end of the probe needs to be in contact with a metal piece or a conductive material in order for the edge finder to light up

- Shank Dia: 3/4"
- Probe Diameter: 0.394"
- Overall Length: 7-1/2"
- Repeatability T.I.R within 0.0002"
- Use 2pcs 1.5V button battery 1pc AG5 battery

Item #0805-3015  
\$83.00/PC



## ELECTRONIC SHORT SHANK EDGE FINDER

Item # C028-9273  
\$92.00/PC

**Features:**

- One piece construction for strength and accuracy.
- Repeatability T.I.R within 0.0002"
- Precision ground on all surfaces.
- Quickly locates work edges.
- Save time positioning.
- Highly visible LED lights.

**SPECIFICATION**

Ball diameter.....0.310"  
Shank diameter.....3/4"  
Overall length.....3.875"

